

MODELLO	DESCRIZIONE	PREZZO
Amplificazione - Preamplificatore Passion RCA	Design: All tube signal section, Single-Ended Architecture Attenuator: 64 step, remote controlled Tubes: 2 x 12AU7 (ECC82) - Every unit comes with select NOS tubes Bandwidth: 10 Hz - 45 KHz +/- 1.0 dB Input: 4 RCA with Single-Ended / 4 XLR with Balanced Model Input impedance: 100 Kohms Gain: 18 dB Output: 2 RCA with single-ended / 2 XLR with balanced model Output impedance: 750 ohms Dimensions: 38.2 x 54.5 x 14.6 cm (WxDxH), excl. feet Weight: 18.9 Kg	€ 29900,00
Amplificazione - Preamplificatore Passion Balanced	Design: All tube signal section, Single-Ended Architecture Attenuator: 64 step, remote controlled Tubes: 2 x 12AU7 (ECC82) - Every unit comes with select NOS tubes Bandwidth: 10 Hz - 45 KHz +/- 1.0 dB Input: 4 XLR with Balanced Model Input impedance: 100 Kohms Gain: 18 dB Output: 2 XLR with balanced model Output impedance: 750 ohms Dimensions: 38.2 x 54.5 x 14.6 cm (WxDxH), excl. feet Weight: 18.9 Kg	€ 34900,00
Amplificazione - Preamplificatore Passion Signature RCA		€ 39800,00
Amplificazione - Finale di potenza Passion Single-Ended	Design: Class A, Zero Feedback, Parallel Single-Ended Architecture Tubes: 2x 845, 2x 6SN7 - Every unit comes with select NOS tubes Bandwidth: 15 Hz - 25 KHz +/- 1.0 dB Input: 1 x RCA (XLR optional) Input impedance: 75 KOhms Input Sensitivity: 1.25 Volts (balanced version 5 Volts) Gain: 21 dB @ 4 ohm, 24 dB @ 8 ohm Output Power: 52 Watts Speaker impedance: 4 - 8 Ohms Dimensions: 38.2 x 62.2 X 29.5 cm (WxDxH), excl. feet	€ 41900,00
Amplificazione - Finale di potenza Passion Balanced Single-Ended	Design: Class A, Zero Feedback, Parallel Single-Ended Architecture Tubes: 2x 845, 2x 6SN7 - Every unit comes with select NOS tubes Bandwidth: 15 Hz - 25 KHz +/- 1.0 dB Input: 1 x RCA ; 1 x XLR Input impedance: 75 KOhms Input Sensitivity: 1.25 Volts (balanced version 5 Volts) Gain: 21 dB @ 4 ohm, 24 dB @ 8 ohm Output Power: 52 Watts Speaker impedance: 4 - 8 Ohms Dimensions: 38.2 x 62.2 X 29.5 cm (WxDxH), excl. feet	€ 46900,00
Amplificazione - Finale di potenza PASSION POWER AMPLIFIER		€ 18000,00
Amplificazione - Finale di potenza Hybrid Monoblock Amplifier		€ 89000,00
Amplificazione - Amplificatore Integrato Passion Integrated Amplifier		N.D.
Amplificazione - Finale di potenza Hybrid Stereo Amplifier		€ 42000,00

## Audioplus Hi End

Via Crispi 77 - 63074 San Benedetto del Tronto (AP) - Tel: 0735.593969 Fax: 0735.575014 - P. IVA 01477140444

Listino generato il 25/04/2024 e valido 7 giorni salvo disponibilità - pagina

1

<p><b>Amplificazione - Preamplificatore</b> <b>Passion Signature Balanced</b></p>	<p>The Signature model is a significant step above the Passion series. Within the signal path, Duelund's select CAST coupling capacitors together with Echole's Signature cabling are incorporated. The Signature Preamplifier's circuitry can utilize E80CC in addition to ECC82 tubes. The power supply has also been re-designed. Critical parts of the signal path utilize NOS resistors that are not readily available in the market. The sonic improvement from the Passion version can be described as being better than ever in terms of naturalness, coherence, with a very convincing sense of realism and emotional communication. Finally, there is a very limited edition Altius model of the Absolare preamplifier. Please contact us for further information about the Altius preamplifier.</p> <p>Design: All tube signal section, Single-Ended Architecture Attenuator: 64 step, remote controlled Tubes: 2 x 12AU7 (ECC82) - Every unit comes with select NOS tubes Bandwidth: 10 Hz - 45 KHz +/- 1.0 dB Input: 4 XLR with Balanced Model Input impedance: 100 Kohms Gain: 18 dB Output: 2 XLR with balanced model Output impedance: 750 ohms Dimensions: 38.2 x 54.5 x 14.6 cm (WxDxH), excl. feet Weight: 18.9 Kg</p>	<p>€ 44000,00</p>
<p><b>Amplificazione - Finale di potenza</b> <b>Passion Signature Single-Ended</b></p>	<p>The Signature series is a significant step above the Passion series. Within the signal path Duelund's select CAST coupling capacitors together with Echole's Signature cabling are utilized. The N.O.S. driver tubes are carefully chosen to align with this new level of purity. The sound is described as being better than ever in terms of naturalness, coherence, with a very convincing sense of realism and emotional communication Finally, there is a very limited edition Altius model available for the Absolare S.E.T. Power amplifiers. Please contact us for further information about the Altius S.E.T. amplifier.</p>	<p>€ 58900,00</p>
<p><b>Amplificazione - Finale di potenza</b> <b>Passion Signature Balanced Single-Ended</b></p>	<p>The Signature series is a significant step above the Passion series. Within the signal path Duelund's select CAST coupling capacitors together with Echole's Signature cabling are utilized. The N.O.S. driver tubes are carefully chosen to align with this new level of purity. The sound is described as being better than ever in terms of naturalness, coherence, with a very convincing sense of realism and emotional communication Finally, there is a very limited edition Altius model available for the Absolare S.E.T. Power amplifiers. Please contact us for further information about the Altius S.E.T. amplifier.</p>	<p>€ 63900,00</p>

## Audioplus Hi End

Via Crispi 77 - 63074 San Benedetto del Tronto (AP) - Tel: 0735.593969 Fax: 0735.575014 - P. IVA 01477140444

Listino generato il 25/04/2024 e valido 7 giorni salvo disponibilità - pagina 2

**Amplificazione - Finale di potenza**  
**Passion PushPull**

Design: Substantially operating in Class A, Zero Feedback, Push-Pull Architecture Tubes: 2x 845, 2x EL34, 1x 12AT7 / ECC81 - Every unit comes with select NOS tubes Bandwidth: 15 Hz - 25 KHz +/- 1.0 dB Input: 1 x RCA (XLR optional) Input impedance: 100 KOhms Input Sensitivity: 1.5 Volts (balanced version 6 Volts) Gain: 21 dB @ 4 ohm, 24 dB @ 8 ohm Output power: 85 Watts Speaker impedance: 4 - 8 Ohms Dimensions: 38.2 x 62.2 X 29.5 cm (WxDxH), excl. feet Weight: 42.0 Kg (each monoblock)

€ 48900,00

**Amplificazione - Finale di potenza**  
**Passion Balanced PushPull**

Design: Substantially operating in Class A, Zero Feedback, Push-Pull Architecture Tubes: 2x 845, 2x EL34, 1x 12AT7 / ECC81 - Every unit comes with select NOS tubes Bandwidth: 15 Hz - 25 KHz +/- 1.0 dB Input: 1 x XLR 1x RCA Input impedance: 100 KOhms Input Sensitivity: 1.5 Volts (balanced version 6 Volts) Gain: 21 dB @ 4 ohm, 24 dB @ 8 ohm Output power: 85 Watts Speaker impedance: 4 - 8 Ohms Dimensions: 38.2 x 62.2 X 29.5 cm (WxDxH), excl. feet Weight: 42.0 Kg (each monoblock)

€ 51900,00

**Amplificazione - Finale di potenza**  
**Passion Signature PushPull**

The Signature series is a significant step above the Passion series. Within the signal path Duelund's select CAST coupling capacitors together with Echole's Signature cabling are utilized. The N.O.S. driver tubes are carefully chosen to align with the new level of purity. .Absolare Signature Push-Pull amplifier's performance is best described as dynamics, realism and truthfulness closest to the live reproduction of music. Finally, there is a very limited edition Altius model of the Push-Pull amplifier. Please contact us for further information about the Altius Push-Pull amplifier.

€ 66000,00

**Amplificazione - Finale di potenza**  
**Passion Signature Balanced PushPull**

The Signature series is a significant step above the Passion series. Within the signal path Duelund's select CAST coupling capacitors together with Echole's Signature cabling are utilized. The N.O.S. driver tubes are carefully chosen to align with the new level of purity. .Absolare Signature Push-Pull amplifier's performance is best described as dynamics, realism and truthfulness closest to the live reproduction of music. Finally, there is a very limited edition Altius model of the Push-Pull amplifier. Please contact us for further information about the Altius Push-Pull amplifier.

€ 70000,00

## Audioplus Hi End

## Amplificazione - Amplificatore Integrato Passion (RCA)

Absolare's production standard. signal and power section utilize Mundorf's custom-matched Silver-Gold-Oil/TubeCap capacitors and Echole's proprietary Obsession-grade Silver/Gold/Palladium alloy wiring. Design: Tube input, Solid State output, Hybrid Architecture Attenuator: 48 step or 64 step, remote controlled Tubes: 2x 12AU7 / ECC82 or 2x E80CC - Every unit comes with select NOS tubes Bandwidth: 15 Hz - 30 KHz +/- 1.0 dB Input: 4 RCA with Single-Ended / 4 XLR with Balanced Model Input impedance: 100 Kohms Input Sensitivity: 0.5 Volts (balanced version 2 Volts) Gain: 37 dB Output power: 150 Watts minimum @ 8 ohms, 200 Watts minimum @ 4 ohms. Speaker impedance: 4 - 8 Ohms Dimensions: 38.2 x 67 X 20 cm (WxDxH), excl. feet Weight: 30 Kg

€ 29700,00

## Amplificazione - Amplificatore Integrato Passion Signature

The Signature series is a significant step above the Passion series. Within the signal path Duelund's select CAST coupling capacitors together with Echole's Signature cabling are utilized. The N.O.S. driver tubes are carefully chosen to align with the new level of purity. Absolare Integrated Signature amplifiers performance is sublime. The Signature Integrated amplifier results in an even faster, more transparent sound with enhanced harmonic resolution.

€ 37000,00

## Componenti Hi-Fi - Accessorio Bybee Purifier-filtro di rete

Absolare Bybee Purifier Type: Passive Electrical Mains Distribution Device. Application: The device is designed supply an entire audio system, including all types of power amplifiers. AC Input: The device can be used with 110-120 Volt AC & 220-240 Volt AC electrical mains supply. There is a 15A circuit breaker. AC Outputs: Available in two versions both with six outlets - (a) six European Schuko AC outlets or (b) three sets of duplex US AC outlets. Components: Oyaide Silver/Palladium coated IEC receptacle. Oyaide Silver/Palladium coated AC outlets. Echole Obsession Signature powercord internal wiring.. Jack Bybee designed non-current limiting EMI/RFI filtering devices. Mundorf custom SilverGold 800AC capacitors. Absolare proprietary resonance control composite treating all. 6 x Custom-Polished Palladium over Silver Oyaide Outlets (US or SCHUKO) Non-Current Limiting Passive design 110 / 240V compatibility No-inductor throughout the design Actual Echole Obsession Signature Powercords employed Dimensions: 48.0 x 39 x 10.0 cm (WxDxH), excl. feet Weight: 13.0 Kg

€ 7900,00

## Audioplus Hi End

Componenti Hi-Fi - Accessorio Bullets	Absolare Bullets Custom-polished Palladium over Silver Termination (Banana or Spade) Aircraft-grade aluminum body Silver-plated Speaker Binding Posts Dimensions: Diameter: 2 cm Length: 16 cm Weight: 85 gr (per unit)	€ 6400,00
Amplificazione - Preamplificatore Fono Passion Phono Stage	Design: All tube signal path, 2 box design (1 power supply, 1 signal). 2 inputs with 6 level cartridge loading Tubes: 3x 12AX7 / ECC83, 2x 12AU7 / ECC82, 4x 6C45PI - Every unit comes with select NOS tubes Bandwidth: 20 Hz - 20 KHz Input A loading: :68 ohm, 150 ohm, 330 ohm, 680 ohm, 47 Kohm, custom value Input B loading: :47 ohm, 100ohm, 220 ohm, 470 ohm, 1 Kohm, custom value Inputcapacitance: 100 pF Gain: 61 dB Output: 1 RCA with single-ended / 1 XLR with balanced model Outputimpedance : :325 ohms Dimensions: 38.2 x 54.5x 14.6 cm (WxDxH), per chassis, excl. feet Weight: 20 Kg (Signal) / 22 Kg (Power Supply)	€ 58000,00

## Audioplus Hi End

Via Crispi 77 - 63074 San Benedetto del Tronto (AP) - Tel: 0735.593969 Fax: 0735.575014 - P. IVA 01477140444

Listino generato il 25/04/2024 e valido 7 giorni salvo disponibilità - pagina 5